

WHAT IS CLAIMED IS:

1. A pro-up netting comprising:

three frame rods, each frame rod being formed by an insertion rod,
an elastic cotton string and a connecting tube; one ends of the
5 insertion rod being reduced as a round cylinder; the connecting tube
being hollowed and one end thereof being formed with a reduced
hollow tube; one end of the insertion rod being connected with the
elastic cotton string; the elastic cotton string of the insertion rod
passing through the reduced hollow tube to the round cylinder of
10 another insertion rod; this connection being repeated so as to extend
the length thereof;

a rope; ends of the rope having respective receptacles; a hole
being formed on each receptacle for receiving the extending means
and frame rod; the rope being a supporting structure;

15 the extending means being formed by two combing rods, each
combing rod having an elastic cotton cord, at least one two-side
sleeve, and at least one single side sleeve; each combing rod being
extended with the elastic cotton cord at one radial center of the one
end thereof; the two-side sleeves and single side sleeves being
20 hollowed; each end of the two-side sleeve and one end of single
side sleeve being large ends which are formed with respective grooves
therein and another end of the single side sleeve being a small end
which forms a sleeve body; the sleeve body being inserted into the

groove; the elastic cotton cord of the combing rod being inserted into the groove of the single side sleeve; then the sleeve body of the single side sleeve being inserted into the groove of another single side sleeve; the process being repeated for connecting a plurality of single
5 side sleeves; then the sleeve body of the last single side sleeve being inserted into the groove in one side of the two-side sleeve; another end of the two-side sleeve being inserted by the sleeve body of another single side sleeve and thus a plurality of single side sleeves being serially connected at two ends of the two-side sleeve;

10 a plurality of buckling rings for fixing the extending means; and
a web;

wherein three frame rods are connected with each frame rod having one end being connected together; and another ends of two selected frame rods are connected to two ends of the extending means
15 and another end of another frame rod is connected to a middle part of the extending means; the extending means being bent like a semi-round shape; the web is connected between each two of the three frame rods.

2. The pro-up netting as claimed in claim 1, wherein the buckling
20 ring is a sleeve cloth.

3. The pro-up netting as claimed in claim 1, wherein the buckling ring is a toggle.

4. The pro-up netting as claimed in claim 1, wherein the rope is replaced by cloth strips.